

QUIET BLANKET QC-124

Quilted Fiberglass Material

2" Thick Fiberglass - Double Faced

Part Number:	QC-124						
Color:	Metallic Gray or White						
Weight:	0.50 lb./sq. ft.; 72 oz./sq. yd.						
Thickness:	2 inch nominal (at loft).						
Roll Size:	48" wide, 25ft. long, Bound edges.						
Construction:	Two layers of 1" thick, 2 lb./cu. ft. density fiberglass batting, quilted between 2 layers of vinyl coated fiberglass facing and non-woven nylon Scrim backing material. Nylon thread.						
Flame Resistance:	Class 1 rated material per ASTM E84 (Surface Burning Characteristics of Building Materials): <table><tr><td><u>Flame spread</u></td><td><u>Fuel Contributed</u></td><td><u>Smoke Developed</u></td></tr><tr><td>5.0</td><td>20.00</td><td>5.0</td></tr></table>	<u>Flame spread</u>	<u>Fuel Contributed</u>	<u>Smoke Developed</u>	5.0	20.00	5.0
<u>Flame spread</u>	<u>Fuel Contributed</u>	<u>Smoke Developed</u>					
5.0	20.00	5.0					
Chemical Resistivity:	Resists oils, grease, moisture, mild acids and alkalis', dirt, dust, and salt atmospheres.						
Clean ability:	Facing can be cleaned, using a damp towel with common industrial cleaners.						
Temperature Limits:	Service range of -20° to +180° F (continuous) + 265° F (intermittent).						
Thermal Conductivity:	K= 0.25 (BTU in./°F - sq. ft. - hr.) @ 75° F mean.						

Random Incidence Sound Absorption:

Frequency (Hertz)						
125	250	500	1000	2000	4000	NRC
.19	.99	.96	.80	.57	.33	.85

(Per ASTM C423-77)

Noise Transmission Loss:

Frequency (Hertz)						
125	250	500	1000	2000	4000	STC
6dB	11dB	15dB	20dB	25dB	32dB	20dB